

CS2 Linear Series



Operating Conditions General Specification:

Operating Temperature -10°C to +40°C

Voltage 48v DC per channel

Storage Temperature -25°C to +70°C

Drive Current 350ma / 500ma

Total Watts 48w at 350mA / 69w at 500mA

Lumens 4080/5520

Maximum Ambient 40°C

CS2 LED Modules

Product Overview:

The CS2 range of linear LED Modules are available in narrow, medium, wide angle beam or as a powerful linear wall washing system with highly efficient optical lenses.

The linear LED Module system can be configured for interior or IP65 exterior applications.

Features:

- Long life – 50,000 hours
- 3200K–5500K, RGB, RGBA & RGBW
- Low energy consumption 40w / mtr
- Fully DMX controlled
- Aluminium profile - 62mm x 23mm
- Optics - 6°, 15°, 25° & 8° x 25°
- Robust construction
- IP65 options
- Simple plug & play installation
- Standard modular lengths
- Adjustable mounting brackets
- Low voltage operation
- Optimised thermal management

Module Lengths:

400mm, 600mm & 1200mm

Electrical:

Input Current : 350mA or 500mA

Maximum Vf : 48 VDC per channel

Compatible driver : DMX

Connection : 1.5m RJ45 cable

Products represented here are IEC825 Class 2 for eye safety. Do not stare into the LED Light beam at close range.

Fixture should only be connected to approved DMX drivers.